

1/15

FIG.1





FIG.3

13 FUNCTION/ SERVICE	14 OPERATION TRANSITION STATE	15 SETTING NUMBERS	16 HELP LIST ADDRESS
COPY	COPY STATE	Y13, Y27, S38, S39	*6000
TRANSMIT	TRANSMITTING STATE	Y5, Y7, Y9, D5, D10, S12, S13, S38, S39	*6010
:	:	:	:
PRESCHEDULED TRANSMIT	PRESCHEDULED TRANSMITTING STATE	Y5, Y7, Y9, Y5, Y9, D5, D10, S12, S13, S38, S39	*6050

2/15

FIG.2



3/15
FIG.4

USER SETTINGS (Y)		DIAL OPTIONS (D)		SERVICEMAN SETTINGS (S)	
01:MCF(SINGLE-LOC.)	ON/OFF	01:REDIAL TRIES	3TRY	01:SERVICE BIT	ON/OFF
02:MCF(MULTI-LOC.)	ON/OFF	02:REDIAL INTERVAL	3MIN	02:MONITOR CONT.	ON/OFF
03:ERR.REPORT(MCF)	ON/OFF	03:DIAL TONE DETECT	ON/OFF	03:COUNTRY CODE	GER
04:IMAGE IN MCF	ON/OFF	04:BUSY TONE DETECT	ON/OFF	04:TIME/DATE PRINT	ON/OFF
05:SENDER ID	ON/OFF	05:MF(TONE)/DP(PULSE)	MF	05:TSI PRINT	ON/OFF
06:MONITOR VOLUME LOW/MID/HIGH		06:PULSE DIAL RATE	10PPS	06:TAD MODE	TYPE2
07:BUZZER VOLUME LOW/MID/HIGH		07:PULSE MAKE RATIO	39%	07:REAL TIME DIAL	TYPE2
08:CLOSED NETWORK	ON/OFF	08:PULSE DIAL TYPE	NORMAL	08:TEL/FAX SWITCH	ON/OFF
09:TX MODE DEFAULT STD/NORMAL		09:MF(TONE)DURATION	100MS	09:MDY/DMY	MDY
10:T/F TIMER PRG.	35SEC	10:PBX LINE	ON/OFF	10:LONG DOC. SCAN	ON/OFF
11:RING RESPONSE	1RING	11:PBX TYPE	NORMAL	11:TONE FOR ECHO	ON/OFF
12:DISTINCTIVE RING	ON/OFF	12:AUTO START	ON/OFF	12:MH ONLY	ON/OFF
13:PAPER SIZE	A4	13:DIAL PREFIX	ON/OFF	13:H/MODEM RATE	33.6K
14:USER LANGUAGE	ENGLISH			14:T1(TX)TIMER VALUE	059
15:INCOMING RING	ON/OFF			15:T1(RX)TIMER VALUE	035
16:REMOTE RECEIVE	ON/OFF			16:T2 TIMER VALUE	130
17:MEM/FEEDER SWITCH MEM.				17:DIS BIT32	ON/OFF
18:POWER SAVE MODE	ON/OFF			18:ERR CRITERION VALUE	10
19:ECM FUNCTION	ON/OFF			19:OFF HOOK BYPASS	ON/OFF
20:REMOTE DIAGNOSIS	ON/OFF			20:NL EQUALIZER	OKM
21:PC/FAX SWITCH	ON/OFF			21:ATTENUATOR	10DB
22:NO TONER MEM. RX	ON/OFF			22:T/F TONE ATT	10DB
23:MEM FULL SAVE	ON/OFF			23:MF. ATT	3DB
24:CONTINUOUS TONE	ON/OFF			24:RING DURA.*	10MS
25:INSTANT DIAL	ON/OFF			25:CML TIMING.*	100MS
26:RESTRICT ACCESS	ON/OFF			26:LED HEAD STROBE	10100
27:WIDTH REDUCTION	ON/OFF			27:MEDIA TYPE	MEDIUM
28:TONER SAVE	ON/OFF			28:TR LATCH CURRENT	0
29:CNG COUNT	1			29:NSF SWITCH	ON/OFF
30:ISDN DIAL MODE	G4			30:ID/TSI PRIORITY	ID
31:SPEECH RECEIVE	ON/OFF			31:TONER COUNT CLEAR	ON/OFF
32:USB CONV. MODE	ON/OFF			32:PARALLEL PICK UP	ON/OFF
33:PAPER SIZE CHECK	ON/OFF			33:V. 34 TX RETRY	ON/OFF
34:PRINT JOB T.O.	30SEC			34:SYMBOL RATE	3429
				35:LEASED LINE	ON/OFF
				36:CED SEND	ON/OFF

4/15

FIG.5

HELP LIST

COMMUNICATION ERROR: ERROR NO. 3122

IF YOU WERE PERFORMING G31 COMMUNICATION USING AN ISDN SWITCH SIMULATOR, THE CAUSE MAY BE THE FOLLOWING.


IN G31 COMMUNICATIONS, MODEM SIGNALS ARE CONVERTED BETWEEN ANALOG AND DIGITAL FORM SO THAT THEY CAN BE TRANSMITTED ON DIGITAL LINES. THERE ARE TWO CONVERSION SYSTEMS: μ -LAW, USED IN THE UNITED STATES AND JAPAN; AND A-LAW, USED IN OTHER COUNTRIES.

OKIFAX-ISDN USES μ -LAW IF THE COUNTRY CODE SETTING (A SERVICEMAN SETTING) IS USA; OTHERWISE, A-LAW IS USED.

CHECK WHICH SYSTEM YOUR SWITCH SIMULATOR USES (IF IT WAS MADE IN JAPAN IT WILL USE μ -LAW), AND RECHECK THE COUNTRY CODE SETTING TO MAKE SURE IT MATCHES YOUR SWITCH'S SYSTEM.


5/15

FIG.6A



6/15

FIG.6B



7/15

FIG.7





FIG.8

34 FUNCTION/ SERVICE	35 OPERATION TRANSITION	36 SETTING NUMBERS	37 HELP LIST ADDRESS
COPY	COPY, [COPY, TIME-OUT]	Y13, Y27, S38, S39	*6000
TRANSMIT	[TEN, OT, AD], START	Y5, Y7, Y9, Y5, Y9, D5, D10, S12, S13, S38, S39	*6010
:	:	:	:
PRESCHEDULED TRANSMIT	FUNC, OT1, YES, TEN, YES, [TEN, OT, AD], START	Y5, Y7, Y9, Y5, Y9, D5, D10, S12, S13, S38, S39	*6050


8/15

FIG.9




9/15

FIG.10A




10/15

FIG.10B



11/15

FIG.10C



12/15

FIG.11





FIG.12

55 FUNCTION/ SERVICE/ ERROR CODE	56 OPERATION TRANSITIONS	57 SETTING NUMBERS	58 HELP LIST ADDRESS
TRANSMIT	[TEN, OT, AD], START	Y5, Y7, Y9, Y5, Y9, D5, D10, S12, S13, S38, S39	*6010
:	:	:	:
PRESCHEDULED TRANSMIT	FUNC, OT1, YES, TEN, YES, [TEN, OT, AD], START	Y5, Y7, Y9, Y5, Y9, D5, D10, S12, S13, S38, S39	*6050
1234 (PAPER SIZE ERROR)		Y13	*7030
BA01(ISDN)		Y30, Y31, S3, S40, S41, S42, S43	*7100


13/15

FIG.13A



14/15

FIG.13B



15/15

FIG.13C

